

Submersible pump

3hp

RH-4034

- Submersible Design Made for submerging in water for lifting and draining.
- Suitable Liquids Clean water, free of solids, abrasives, impurities. Non-viscous, non-aggressive, non-crystallized, similar to water in physical and chemical properties.
- Applications Domestic use, drainage, lifting water from tanks, rivers, pools. Irrigation of gardens and allotments.
- Automatic Level Control Equipped with float switch for automatic water level and pump operation control.
- Motor Protection IP68 protection level, thermal protector, Class B insulation for extended motor life.
- Durable Construction Ceramic/graphite mechanical seal,PPO impeller, cast iron pump housing for increased efficiency.
- S1 Duty Cycle Motor Contributes to overall pump durability



Model	RH-4034
Power	3hp
Voltage	220V
Frequency	50Hz
Min.Flow	2ml/h
Max. Flow	9ml/h
Min.Head	0.3m
Max. head	58m
Inlet/outlet port diameter	"2
Speed	2850RPM
Max. liquid temperature	0-35
Max. Ambient temperature	0-40
solid passage diameter	4mm
max immersion depth	5m
max dry running time	10Sec
Protection level	IP68
Insulation Class	B
Pump housing material	CAST IRON

Motor housing material	S/S 201
Mechanical seal material	SIC-SIC/Ceramic-Graphite
Coil winding material	COPPER
Impeller material	PPO
shaft material	316+45
Weight	26.2kg
Supplied In	honeycomb carton