

Submersible Sewage Pump
2HP

RH-4041

- Pump design to be immersed in water for lifting and draining water
- Suitable for clean water and free of solids and abrasives, non-viscous, nonaggressive, non-crystallised and other liquids similar to water in physical and chemical properties
- Properly in domestic, drainage or lifting water from the tanks or river or pool, irrigation of gardens and allotments usage
- Pumps equipped with float switch for automatically controlling water level and pump operation
- Provides with Protection level IP68 Thermal protector and insulation Class B to ensure motor long life
- More efficiency by using Ceramic/Graphite mechanical seal, CAST IRON impeller, CAST IRON pump housing
- The motor duty cycle type S1 lead to increase durability



| | |
|----------------------------|---------------------|
| Model | RH-4041 |
| Power | 2HP |
| Voltage | 220V |
| Frequency | 50Hz |
| Min.Flow | 5m ³ /h |
| Max.Flow | 36m ³ /h |
| Min.Head | 2m |
| Max.Head | 13.5m |
| Inlet/Outlet Port Diameter | 3" |
| Speed | 2850RPM |
| Max.Liquid Temperature | 0-35°C |
| Max.Ambient Temperature | 0-40°C |
| Working Pressure | 0-1.35BAR |
| Solid Passage Diameter | 25mm |

| | |
|--------------------------|--------------------------|
| Max Immersion Depth | 5m |
| Max Dry Running Time | 30Seconds |
| Protection Level | IP68 |
| Insulation Class | B |
| Pump Housing Material | CAST IRON |
| Motor Housing Material | S/S 304 |
| Mechanical Seal Material | SIC-SIC/Ceramic-Graphite |
| Coil Winding Material | COPPER |
| Impeller Material | CAST IRON |
| Shaft Material | 316+45 |
| Weight | 26.4kg |
| Supplied in | Honeycomb Carton |