

Submersible Sewage Pump

750W-8.5m

RH-4042

- Submersible pump design to be immersed in water for lifting and draining water
- Suitable for pumping dirty water, discharging domestic waste water that containing suspended solids up to a maximum of 35mm
- Pumps equipped with float switch for automatically controlling water level and pump operation
- Provides with Protection level IPX8 Thermal protector and insulation Class B to ensure motor long life
- More efficiency by using Ceramic/Graphite mechanical seal, PA66 impeller,PP pump housing
- The motor duty cycle type S1 lead to increase durability
- All the exposed screw is stainless steel material
- Stainless steel motor cover and shaft to extend the life time
- Oil submerged lip seal and mechanical seal makes the sealing more reliable
- High strength engineering plastic pump body



Model	RH-4042
Power	750W
Voltage	220-240V
Frequency	50Hz
Min.Flow	0
Max.Flow	13000L/h
Min.Head	0
Max.Head	8m
Outlet Port Diameter	G1-1/2"
Speed	2850RPM
Max.Liquid Temperature	35°C
Max.Ambient Temperature	35°C

Working Pressure	0.8Bar
Solid Passage Diameter	35mm
Max Immersion Depth	7m
Max Dry Running Time	30Seconds
Protection Level	IP×8
Insulation Class	B Class
Pump Housing Material	PP
Motor Housing Material	409#Stainless Steel
Mechanical Seal Material	Ceramic and Graphite
Motor Protection	125°C
Coil Winding Material	Copper Winding
Impeller Material	PA66
Shaft Material	420#Stainless Steel
Net Weight	5.1Kg
Gross Weight	5.5Kg
Packaging	Color Box
Includes	Adaptor×1, Manual×1