

## **POWER TOOLS**

## **RH-4782**

## **Gasoline Generator** 5500W

- 420 cc, 4-Stroke 8600w engine with considerable performance
- 25 Liter full steel fuel tank provides up to 8.6 hours of run time
- Special compact designfor ease of use and better portability
- Circuit breaker outlets for added protection
- Minimum sound and vibration in indoor usage
- 100% copper-wound generator head allows continuous operation without overheating
- Includes one (12V) DC outlets
- Ideal for workshops and light-duty industrial usage

Model	RH-4782	
Generator	Туре	Gasoline Generator
	AC Voltage	220V
	Rated Amperage	23A
	Frequency	50Hz
	Max. Output	5.5KW
	Rated Output	5KW
	Power Factor	1
	DC Output	DC 12V, 8.3A
Engine	Model	FC190F
	Туре	Single Cylinder, 4-Stroke, Forced Air Cooled
	Bore×Stroke	90mm×66mm
	Displacement	420cc
	Max. Output	8.6KW/3600RPM
	Fuel	Gasoline
	Fuel tank Capacity	25 Lit
	Rated Continuous Operation	8.6 hr
	Lubricating Oil	SAE 10W-30
	Lubricating Oil Capacity	1.1 Liter
	Starting System	Recoil & E-start
	Ignition System	T.C.I
	Spark Plug: Type	F7TC/F7RTC





















## **POWER TOOLS**

Engine	Maximum Fuel consumption Rate	2.9 Lit/hr
Dimension	Net Dimension LxWxH	686×516×560mm
	Overall Dimension LxWxH	740×575×625mm
	Net Weight	82Kg
	Gross Weight	84Kg
Supplied in	Carton	
Include	2 Plug, 1 Spark Plug Sleeve, 1 Rod, 12V DC Output Clip, 2 key, 1 Set Wheels and Handles	